

# C6 Frontage Standards

## C6.1 FRONTAGE STANDARDS

A

### Purpose

This Section sets forth the standards applicable to the development of private frontages. Private frontages are the components of a building that provide an important transition and interface between the public realm (street and sidewalk) and the private realm (yard or building). These standards supplement the standards for each zone that the frontage types are allowed within. For each frontage type, a description, a statement of the type's intent, and design standards are provided. These standards are intended to ensure that proposed development is consistent with the City's goals for building form, physical character, land use activity and quality.

B

### Applicability

These standards work in combination with the standards found in Section C4 (Development Standards by Zones) and Section C5 (Building Types) and are applicable to all private frontages within transect zones.

C

### Allowed Frontage Types

Table C6.1 (Frontage Types) provides an overview of the allowed frontage types.





Table C6.1. Frontage Types.

**Front Yard:** A frontage wherein the facade is set back substantially from the frontage line. The front yard created remains unfenced and is visually continuous with adjacent yards, supporting a common landscape. The setback can be densely landscaped to buffer from the higher speed thoroughfares.

**Porch:** A frontage wherein the facade is set back from the frontage line with an attached porch permitted to encroach. A fence at the frontage line maintains the demarcation of the yard while not blocking view into the front yard. The porches shall be no less than 8 feet deep.

**Dooryard:** A frontage wherein the facade is set back from the frontage line with an elevated garden or terrace permitted to encroach. This type can effectively buffer residential quarters from the sidewalk, while removing the private yard from public encroachment. The terrace is also suitable for cafes.

**Stoop:** A frontage wherein the facade is aligned close to the frontage line with the first story elevated from the sidewalk sufficiently to secure privacy for the windows. The entrance is usually an exterior stair and landing. This type is recommended for ground-floor residential use.

**Forecourt:** A frontage wherein a portion of the facade is close to the frontage line and the central portion is set back. The forecourt with a large tree offers visual and environmental variety to the urban street streetscape. The forecourt may accommodate a vehicular drop-off.

**Lightcourt:** A frontage wherein the facade is setback from the frontage line by a sunken lightcourt. This type buffers residential use from urban sidewalks and removes the private yard from public encroachment.

**Shopfront:** A frontage wherein the facade is aligned close to the frontage line with the building entrance at sidewalk grade. This type is conventional for retail use. It has substantial glazing on the sidewalk level and an awning that may overlap the sidewalk.



**Gallery:** A frontage wherein the facade is aligned close to the frontage line with an attached cantilevered shed or a lightweight colonnade overlapping the sidewalk. This type is conventional for retail use. The gallery shall be no less than 10 feet wide and may overlap the whole width of the sidewalk to within 2 feet of the curb.


**Arcade:** A frontage wherein the facade is a colonnade that overlaps the sidewalk, while the facade at sidewalk level remains at the frontage line. This type is conventional for retail use. The arcade shall be no less than 12 feet wide and may overlap the whole width of the sidewalk to within 2 feet of the curb.

## C6.2 FRONTAGE TYPES

### A Front Yard

- |   |                 |  |
|---|-----------------|--|
| 1 | Description     | In the Front Yard Frontage Type, the main facade of the building has a large planted setback from the frontage line providing a buffer from the street. The front yard created remains unfenced and is visually continuous with adjacent yards, supporting a common landscape and working in conjunction with the other private frontages. |
| 2 | Size            | Depth 20 ft. min.  |
| 3 | Design Standard | Fences between front yards or between the sidewalk and front yard are not allowed. Front yards could be used in conjunction with another allowed frontage type, such as the Porch.   |






**B Porch**

- |                             |                 |  |       |            |       |            |        |            |                             |             |                |                |                |                 |
|-----------------------------|-----------------|--|-------|------------|-------|------------|--------|------------|-----------------------------|-------------|----------------|----------------|----------------|-----------------|
| 1                           | Description     | The Porch frontage provides a physical transition from the sidewalk to the private lot and building while maintaining visual connection between buildings and the public space of the street. The porch frontage consists of a building with a front set back from the property line and a porch encroaching into that front setback.                              |       |            |       |            |        |            |                             |             |                |                |                |                 |
| 2                           | Size            | <table border="0"> <tr> <td>Width</td> <td>8 ft. min.</td> </tr> <tr> <td>Depth</td> <td>6 ft. min.</td> </tr> <tr> <td>Height</td> <td>8 ft. min.</td> </tr> <tr> <td>Finish level above sidewalk</td> <td>18 in. min.</td> </tr> <tr> <td>Furniture area</td> <td>4 ft. by 6 ft.</td> </tr> <tr> <td>Path of travel</td> <td>3 ft. wide min.</td> </tr> </table> | Width | 8 ft. min. | Depth | 6 ft. min. | Height | 8 ft. min. | Finish level above sidewalk | 18 in. min. | Furniture area | 4 ft. by 6 ft. | Path of travel | 3 ft. wide min. |
| Width                       | 8 ft. min.      |  |       |            |       |            |        |            |                             |             |                |                |                |                 |
| Depth                       | 6 ft. min.      |  |       |            |       |            |        |            |                             |             |                |                |                |                 |
| Height                      | 8 ft. min.      |  |       |            |       |            |        |            |                             |             |                |                |                |                 |
| Finish level above sidewalk | 18 in. min.     |  |       |            |       |            |        |            |                             |             |                |                |                |                 |
| Furniture area              | 4 ft. by 6 ft.  |  |       |            |       |            |        |            |                             |             |                |                |                |                 |
| Path of travel              | 3 ft. wide min. |  |       |            |       |            |        |            |                             |             |                |                |                |                 |
| 3                           | Design Standard | Projecting porches must be open on three sides and have a roof.  |       |            |       |            |        |            |                             |             |                |                |                |                 |

## C Dooryard

- |                             |                  |  |       |            |        |             |                             |                  |                             |            |                |                 |
|-----------------------------|------------------|--|-------|------------|--------|-------------|-----------------------------|------------------|-----------------------------|------------|----------------|-----------------|
| 1                           | Description      | In the Dooryard Frontage Type, the main facade of the building is set back a small distance and the frontage line is defined by a low wall or hedge, creating a small dooryard. The dooryard shall not provide public circulation along a ROW. The dooryard may be raised, sunken, or at grade and is intended for ground-floor residential. |       |            |        |             |                             |                  |                             |            |                |                 |
| 2                           | Size             | <table border="0"> <tr> <td>Width</td> <td>8 ft. min.</td> </tr> <tr> <td>Length</td> <td>50 ft. max.</td> </tr> <tr> <td>Finish level above sidewalk</td> <td>3 ft. 6 in. max.</td> </tr> <tr> <td>Finish level below sidewalk</td> <td>6 ft. max.</td> </tr> <tr> <td>Path of travel</td> <td>3 ft. wide min.</td> </tr> </table>          | Width | 8 ft. min. | Length | 50 ft. max. | Finish level above sidewalk | 3 ft. 6 in. max. | Finish level below sidewalk | 6 ft. max. | Path of travel | 3 ft. wide min. |
| Width                       | 8 ft. min.       |  |       |            |        |             |                             |                  |                             |            |                |                 |
| Length                      | 50 ft. max.      |  |       |            |        |             |                             |                  |                             |            |                |                 |
| Finish level above sidewalk | 3 ft. 6 in. max. |  |       |            |        |             |                             |                  |                             |            |                |                 |
| Finish level below sidewalk | 6 ft. max.       |  |       |            |        |             |                             |                  |                             |            |                |                 |
| Path of travel              | 3 ft. wide min.  |  |       |            |        |             |                             |                  |                             |            |                |                 |
| 3                           | Design Standard  | For live/work, retail and service uses, these standards are to be used in conjunction with those for the Shopfront Frontage Type. In case of conflict between them, the Dooryard Frontage Type standards shall prevail. Shall not be used for circulation for more than one ground floor entry.  |       |            |        |             |                             |                  |                             |            |                |                 |







### D Stoop

- |                             |                        |   |       |                        |       |                        |                             |             |
|-----------------------------|------------------------|---|-------|------------------------|-------|------------------------|-----------------------------|-------------|
| 1                           | Description            | In the Stoop Frontage Type, the main facade of the building is near the frontage line and the elevated stoop engages the sidewalk. The stoop shall be elevated above the sidewalk to ensure privacy within the building. Stairs or ramps from the stoop may lead directly to the sidewalk or may be side-loaded. This Type is appropriate for residential uses with small setbacks. |       |                        |       |                        |                             |             |
| 2                           | Size                   | <table border="0"> <tr> <td style="padding-right: 20px;">Width</td> <td>5 ft. min.; 8 ft. max.</td> </tr> <tr> <td>Depth</td> <td>5 ft. min.; 8 ft. max.</td> </tr> <tr> <td>Finish level above sidewalk</td> <td>18 in. min.</td> </tr> </table>   | Width | 5 ft. min.; 8 ft. max. | Depth | 5 ft. min.; 8 ft. max. | Finish level above sidewalk | 18 in. min. |
| Width                       | 5 ft. min.; 8 ft. max. |   |       |                        |       |                        |                             |             |
| Depth                       | 5 ft. min.; 8 ft. max. |   |       |                        |       |                        |                             |             |
| Finish level above sidewalk | 18 in. min.            |   |       |                        |       |                        |                             |             |
| 3                           | Design Standard        | <ul style="list-style-type: none"> <li>a. Stairs may be perpendicular or parallel to the building facade.</li> <li>b. Ramps shall be parallel to facade or along the side of the building.</li> <li>c. The entry doors are encouraged to be covered or recessed to provide shelter from the elements.</li> </ul>  |       |                        |       |                        |                             |             |

## E Forecourt

- |                        |                 |  |       |             |       |             |                        |          |
|------------------------|-----------------|--|-------|-------------|-------|-------------|------------------------|----------|
| 1                      | Description     | In the Forecourt Frontage Type, the main facade of the building is at or near the frontage line and a small percentage is set back, creating a small court space. The space could be used as an entry court or shared garden space for apartment buildings, or as an additional shopping or restaurant seating area within retail and service areas. |       |             |       |             |                        |          |
| 2                      | Size            | <table border="0"> <tr> <td style="padding-right: 20px;">Width</td> <td>12 ft. min.</td> </tr> <tr> <td>Depth</td> <td>12 ft. min.</td> </tr> <tr> <td>Ratio, height to width</td> <td>2:1 max.</td> </tr> </table>  | Width | 12 ft. min. | Depth | 12 ft. min. | Ratio, height to width | 2:1 max. |
| Width                  | 12 ft. min.     |  |       |             |       |             |                        |          |
| Depth                  | 12 ft. min.     |  |       |             |       |             |                        |          |
| Ratio, height to width | 2:1 max.        |  |       |             |       |             |                        |          |
| 3                      | Design Standard | The proportions and orientation of these spaces should be carefully considered for solar orientation and user comfort.   |       |             |       |             |                        |          |






### F Lightcourt


- |   |                 |  |            |
|---|-----------------|--|------------|
| 1 | Description     | In the Lightcourt Frontage Type, the main facade of the building is set back from the frontage line by an elevated terrace or a sunken lightcourt. This Type buffers residential, retail or service uses from urban sidewalks and removes the private yard from public encroachment. |            |
| 2 | Size            | Width  | 5 ft. min. |
|   |                 | Height, landing above sidewalk   | 6 ft. max. |
|   |                 | Height, landing below sidewalk   | 6 ft. max. |
| 3 | Design Standard | A short fence may be placed along the built-to-line or setback where it is not defined by a building.  |            |



## G Shopfront

- |                                       |                      |   |                           |                      |                                       |             |               |            |
|---------------------------------------|----------------------|---|---------------------------|----------------------|---------------------------------------|-------------|---------------|------------|
| 1                                     | Description          | In the Shopfront Frontage Type, the main facade of the building is at or near the frontage line with an at-grade entrance along the public way. This Type is intended for retail use. It has substantial glazing at the sidewalk level and typically includes an awning that may overlap the sidewalk. It may be used in conjunction with other frontage types. An awning that extends over the sidewalk requires an encroachment permit.   |                           |                      |                                       |             |               |            |
| 2                                     | Size                 | <table border="0"> <tr> <td style="padding-right: 20px;">Ground floor transparency</td> <td>75% of frontage min.</td> </tr> <tr> <td>Shopfront recessed from property line</td> <td>12 ft. min.</td> </tr> </table>   | Ground floor transparency | 75% of frontage min. | Shopfront recessed from property line | 12 ft. min. |               |            |
| Ground floor transparency             | 75% of frontage min. |   |                           |                      |                                       |             |               |            |
| Shopfront recessed from property line | 12 ft. min.          |   |                           |                      |                                       |             |               |            |
| 3.                                    | Awning               | <table border="0"> <tr> <td style="padding-right: 20px;">Depth</td> <td>4 ft. min.</td> </tr> <tr> <td>Setback from curb</td> <td>2 ft. min.</td> </tr> <tr> <td>Height, clear</td> <td>8 ft. min.</td> </tr> </table>  | Depth                     | 4 ft. min.           | Setback from curb                     | 2 ft. min.  | Height, clear | 8 ft. min. |
| Depth                                 | 4 ft. min.           |   |                           |                      |                                       |             |               |            |
| Setback from curb                     | 2 ft. min.           |   |                           |                      |                                       |             |               |            |
| Height, clear                         | 8 ft. min.           |   |                           |                      |                                       |             |               |            |
| 4                                     | Design Standard      | <ol style="list-style-type: none"> <li>a. Shopfront glass shall be clear without reflective glass frosting or dark tinting.</li> <li>b. Shopfront windows may have clerestory windows (horizontal panels) between the shopfront and second floor/top of single-story parapet. Glass in clerestory may be of a character to allow light, while moderating it such as stained glass, glass block, painted glass, or frosted glass.</li> <li>c. Shopfronts with accordion-style doors/windows or other operable windows that allow the space to open to the street are encouraged.</li> <li>d. Operable awnings are encouraged.</li> </ol> |                           |                      |                                       |             |               |            |







### H Gallery

1	Description	A Gallery is a roof or deck projecting from the facade of a building, supported by columns located just behind the street curb. Galleries shelter the sidewalk with a roof or unenclosed, accessible, out-door space making them ideal for retail use. Galleries may be one- or two-stories in height, functioning as covered or uncovered porches at the second floor. Railing on top of the gallery is only required if the gallery roof is accessible as a deck.										
2	Size	<table border="0"> <tr> <td style="padding-right: 20px;">Depth</td> <td>8 ft. min.</td> </tr> <tr> <td>Ground floor height</td> <td>12 ft. min.</td> </tr> <tr> <td>Upper floor height</td> <td>10 ft. max.</td> </tr> <tr> <td>Height</td> <td>2 stories max.</td> </tr> <tr> <td>Setback from curb</td> <td>1 ft. min., 2 ft. max.</td> </tr> </table>	Depth	8 ft. min.	Ground floor height	12 ft. min.	Upper floor height	10 ft. max.	Height	2 stories max.	Setback from curb	1 ft. min., 2 ft. max.
Depth	8 ft. min.											
Ground floor height	12 ft. min.											
Upper floor height	10 ft. max.											
Height	2 stories max.											
Setback from curb	1 ft. min., 2 ft. max.											
3	Design Standard	<ol style="list-style-type: none"> <li>a. Galleries shall be combined with the Shopfront frontage type.</li> <li>b. Galleries must have consistent depth along a frontage.</li> <li>c. Ceiling light is encouraged.</li> <li>d. Galleries may be entirely on private property or may encroach over the sidewalk in the public right-of-way, subject to an encroachment permit prior to issuance of a building permit.</li> <li>e. Column spacing and colonnade detailing, including lighting, shall be consistent with the style of the building to which it is attached.</li> <li>f. Columns shall be placed in relation to curbs so as to allow passage around and to allow for passengers of cars to disembark.</li> </ol>										

## I Arcade

- |   |                 |  |
|---|-----------------|--|
| 1 | Description     | Arcade frontages are composed of a building with ground floor facades which align with the property line, and upper floors which project over the property line to cover the sidewalk. A colonnade structurally and visually supports the building mass which encroaches into the public right-of-way. Arcades contain ground-floor storefronts, making them ideal for retail use as the arcade shelters the pedestrian and shades the storefront glass, preventing glare that might obscure views of merchandise.   |
| 2 | Size            | <p>Depth 8 ft. min.</p> <p>Ground floor height 12 ft. min.</p> <p>Upper floor height 10 ft. min.</p> <p>Setback from curb 1 ft. min., 2 ft. max.</p>   |
| 4 | Design Standard | <p>a. Arcades shall be combined with the Shopfront frontage type.</p> <p>b. Arcades may be entirely on private property or may encroach over the sidewalk in the public right-of-way, subject to an encroachment permit prior to issuance of a building permit.</p> <p>c. Column spacing and colonnade detailing, including lighting, shall be consistent with the style of the building to which it is attached.</p> <p>d. Columns shall be placed in relation to curbs so as to allow passage around and to allow for passengers of cars to disembark.</p> |





# Mix n' Grill

Unit A  
mix your own cereal bowl  
classic comfort food  
mix your own grilled cheese  
mix your own

OPEN

ASK ABOUT OUR CATERING!

HONEY INDUSTRIAL

46

6

LA MONARCA BAKERY & CAFE