

## **CITY OF SOUTH PASADENA**

Public Works Department

1414 Mission Street - South Pasadena - Ca. 91030 - (626) 403-7240
publicworkspermits@southpasadenaca.gov

## EXCAVATIONS FOR SEWER REPAIR/INSTALLATION

Perr	mit Number:			
Wye Sado	Idle Connection \$413.00 \$			
Sure	rety Bond/Deposits: (as required) \$	Т	OTAL: \$	
Own	ners Name:			
	lress:			
City:		State:	Zip:	
Tele	<del></del>	fax:		
Cont	ntractor:			
Addr	lress:			
City:	<u> </u>	State:	Zip:	
Tele				
City	Bus. Lic. No.:	State Lic. N	No.:	
Exc	cavation Dates - from:	to:_		
Loc	cation:			
	<b>New Connection:</b> □ Saddle, □ V			
	<b>Repair:</b> □ Saddle, □ Wye, □ S	ervice Lateral		
Des	scription:			
A co	opy of the following current items are required Certificate of General Liability Insurance N Additional Insured. (minimum combined li	Naming The City	Of South Pasader	na As
	Certificate of Workmen's Compensation In	nsurance.		DIGALERT
	U.S.A. #:			
		go 1 of 2		800-227-2600

## The Applicant Agrees To The Following Conditions When This Permit Is Issued:

- 1. No work shall be done on public property until a permit has been issued.
- 2. No tree roots shall be cut without prior approval from the City Engineer.
- 3. When any trench is greater than (5) feet in depth the following will be required:
  - A. Shoring per CAL-OSHA requirements.
  - B. A ladder must be kept within the trench for access.
- 4. All streets must be saw cut before installing temporary patch.
- 5. No tunneling except under curbs and gutters as approved by the City.
- 6. Dirt left in the public right-of-way will be removed by the Street Division without notice.
- 7. No overnight storage or construction in the roadway without prior approval of the City Engineer.
- Approved lighted barricades are required day and night on a trench which does not have a patch and on any material which is temporarily stored in the public right-of-way.
- 9. Whenever two-directional traffic is reduced to less than eighteen (18) feet a flagman will be required. Traffic control shall conform to the Work Area Traffic Control Handbook (W.A.T.C.H. Manual).
- 10. A temporary patch is required and must be installed by the applicant immediately after the trench is back-filled. Defective patches will be replaced by the City at the contractor's expense.
- 11. Compaction required as specified below and is subject to approval by City Engineer:
  - A. Contractor may elect to backfill with imported or excavated soil. All soil must be approved by a Soil Engineer and compaction methods shall be as directed by the Engineer. Compaction reports shall be required. Minimum compaction shall be 90-95 percent per "Greenbook" Standards. or
  - B. Contractor may elect to backfill with Class-2 c.a.b. material. or
  - C. Contractor may use a minimum 1-sack concrete slurry as backfill per "Greenbook" Standards. No reports required if this method is used.
- 12. Material and method of construction shall conform to applicable sections of the "Greenbook" Standards and by additional conditions as may be attached specifically to the project by the City Engineer.
- 13. New saddle connections shall be core-drilled into existing sewer mains or as approved by the City Engineer.
- 14. Any connections to the City's sewer main shall required video inspection of completed connection.
- 15. Any overtime costs incurred by the City (As related to the permitted work) shall be paid for by the contractor.

Applicant's S	ignature	e:	Date:						
** For Office Use Only **									
Approved	or	Denied (circle one)	Ву:	Date:					
Initial Inspect	ion By:		Date:	-					
Comments:									
					_ _				